

1 SP 17-26



: 12A01926

EN 1.4301 (AISI 304),

15 kW MS6000

40°C.

Grundfos Tempcon,  
MP204  
(DOL).



Grundfos SP

Grundfos



( y)

ppm ( x).



NBR ( ),

, Grundfos  
90°C.

FKM ( ),

NEMA

NTC

Grundfos Tempcon,

Grundfos MP204.

MP204

: 40 °C

0,15 m/sec: 40 °C

Liquid temperature during operation: 20 °C

998.2 kg/m³

: 2900 rpm

: 14 m³/h

: 241 m

: CER/CARNBR

: CE,GOST2

: ISO9906:2012 3B

T40

EN 1.4301

AISI 304

EN 1.4301

AISI 304

DIN W.-Nr. 1.4301


AISI 304

RP2 1/2

6 inch

MS6000  
- 2: 15 kW  
( 2), : 15 kW  
50 Hz  
3 x 380-400-415 V  
34.5-33.5-33.5 A  
490-540-570 %  
cos phi - : 0.85-0.82-0.79  
2860-2870-2880 rpm  
(IEC 34-5): IP68  
(IEC 85): F  
, MEI : 0.70  
ErP status: EuP Standalone/Prod.  
95.4 kg  
133 kg  
0.338 m3  
Danish VVS No.: 388336260

|                                      |                    |
|--------------------------------------|--------------------|
| No.:                                 | SP 17-26           |
| EAN                                  | 12A01926           |
|                                      | 5700391131851      |
|                                      | 2900 rpm           |
|                                      | 14 m³/h            |
|                                      | 241 m              |
|                                      | 26                 |
|                                      | NONE               |
|                                      | CER/CARNBR         |
|                                      | CE,GOST2           |
|                                      | ISO9906:2012 3B    |
|                                      | B                  |
|                                      | YES                |
|                                      | T40                |
|                                      | EN 1.4301          |
|                                      | AISI 304           |
|                                      | EN 1.4301          |
|                                      | AISI 304           |
|                                      | DIN W.-Nr. 1.4301  |
|                                      | AISI 304           |
|                                      | RP2 1/2            |
|                                      | 6 inch             |
|                                      | 40 °C              |
|                                      | 40 °C              |
| 0,15 m/sec:                          |                    |
| Liquid temperature during operation: | 20 °C              |
|                                      | 998.2 kg/m³        |
|                                      | MS6000             |
|                                      | GRUNDFOS           |
|                                      | 15 kW              |
| - 2:                                 |                    |
| ( 2),                                | 15 kW              |
|                                      | 50 Hz              |
|                                      | 3 x 380-400-415 V  |
|                                      | 34.5-33.5-33.5 A   |
|                                      | 490-540-570 %      |
| cos phi -                            | 0.85-0.82-0.79     |
|                                      | 2860-2870-2880 rpm |
|                                      | (IEC 34-5): IP68   |
|                                      | (IEC 85): F        |





Email:

+359 886 190 680  
office@pumpoffice.com  
14.3.2018

No: 78195516

:

, MEI : 0.70

ErP status: EuP Standalone/Prod.


: 95.4 kg

: 133 kg

: 0.338 m3


Danish VVS No.: 388336260

## 12A01926 SP 17-26 50 Hz



! [mm],

12A01926 SP 17-26 50 Hz



|        |       |
|--------|-------|
| U1, W2 | Brown |
| V1, U2 | Black |
| W1, V2 | Grey  |